

CANTER

FE130

SPECIFICATIONS

A boost for your business and your bottom line. The Canter® will change the way you think about moving your company forward. Its cost-of-ownership is so low you can measure it by the mile—in dramatically improved fuel economy, service intervals, payload capacity and driver productivity. Its fuel-injected diesel engine and automated manual transmission set new benchmarks for efficiency and driving ease. They're backed by our industry-best 5-Year/175,000-Mile powertrain limited warranty. The Canter FE130. It's just the boost your business needs.



Weight ratings	GVWR/GCWR	13,200 lb./20,915 lb.			
	GAWR (front/rear)	5,360 lb./9,880 lb.			
Curb weight	Base model	5,225 lb. (est.)			
Body/Payload	Estimated max.	7,975 lb. (see dealer for details)			
Dimensions	Wheelbase	110.2	133.9"	151.6"	169.3"
	Overall length (cab/chassis)	204.1"	227.8"	245.5"	263.2"
	Usable cab to rear axle	81.2"	104.9"	122.6"	140.3"
	Body sizes accommodated	10' to 20'			
	Model	4P10(T5)			
Engine	Type	DOHC, 4-cylinder, 4-stroke cycle, water-cooled, turbocharged, intercooled diesel with 4 valves per cylinder			
	Displacement	183 cu. in. (3.0 L)			
	Max. output (SAE, gross)	161 hp @ 3,400 rpm			
	Max. torque (SAE, gross)	295 lb.-ft. @ 1,300 rpm			
Air cleaner	Type	Dry paper element with snorkel			
Transmission	Standard equipment	Mitsubishi Fuso DUONIC® 6-speed OD AMT			
Axle capacity	Front	5,735 lb.			
	Rear	9,925 lb.			
Final reduction gear	Type	Single-reduction hypoid			
	Ratio (std/opt'l)	4.875/5.285			
Top speed, est.	Std diff/Opt'l diff	90/83 mph			
Turning diameter	Minimum, by wheelbase	34.1'	40.0'	44.6'	49.5'
Tires (premium)	Configuration	Single front, dual rear			
	Size/Type	215/85R16 10PR: LR:E/All-season all positions			
Wheels	Size/Configuration	16" x 6"/5-lug			
Steering	Type	Ball-nut type with integral-type hydraulic power boost			
	Adjustments	Tilt/telescoping steering column with steering lock			
Suspension	Front	Laminated leaf springs with shock absorbers and stabilizer bar			
	Rear	Laminated leaf springs with shock absorbers			
Brakes	Service	Dual-caliper discs, vacuum/hydraulic-type with ABS			
	Parking	Drum/driveline, internal expanding shoe			
	Exhaust	Electrically actuated			
Frame	Type	Ladder/straight			
	Section modulus	7.08 cu. in. per rail			
	Yield strength	56,565 psi			
	RBM per rail	400,410 lb.-in.			
	Height/Width	32.5"/ 33.5"			
Fuel tank	Capacity/Location—std.*	30 gal./in-frame, aft of rear axle			
	Capacity/Location—opt.**	33 gal./left side			
DEF tank	Capacity/Location	3.2 gal./right side			
Battery	Type/Capacity	Two 12-volt, maintenance-free/750 CCA			
Electrical	Starter/Alternator	12-volt/12-volt, 140A output			
Starting	Cold weather provision	Individual ceramic-tipped glow plugs			
Convenience/ Assurance	Windows/Door locks	Power-operated, one-touch up and down driver's-side window			
	Cruise control	Standard (programmable)			
	Entry	Keyless, with driver/assistant door lock control			
	Radio	Optional Clarion AM/FM/CD Bluetooth radio			
	Engine Protection System (EPS)	Automatic engine shutdown due to low oil pressure; automatic fuel reduction due to excessive coolant temperature			
	Idle Limit System (ILS)—opt.	Automatic engine shutdown of stationary vehicle, in Park or Neutral, after achieving normal operating temperature with dealer-programmed limit of 3, 5, or 10 minutes			

SAFETY

Crush bar in each door, energy-absorbing steering column, daytime running lights, dual-caliper disc brakes with ABS (all wheels), covered open-grate entry steps, forward-swing doors for safer entry/exit, high-visibility halogen headlamps, Engine Protection System (EPS)

CAB COLORS

ARCADIA SILVER

NATURAL WHITE

JUPITER GREEN

MARS RED

SHANNON BLUE

SOLID BLACK

All models are available immediately in white. Other colors shown (except Solid Black) may be special-ordered at no extra charge. Accuracy of indicated hues is limited by paper/electronic reproduction.

FABRIC STYLE

BLUE CLOTH

Vehicle specifications are subject to change without notice. Photos and descriptions included in this spec sheet may vary in comparison to actual vehicle models. For warranty limitations and details, see your local dealer.

PRINTED IN THE U.S.A. 5/14.
©2014 MITSUBISHI FUSO TRUCK OF AMERICA, Inc.

Mitsubishi Fuso Truck of America, Inc.

2015 Center Square Road
Logan Township, NJ 08085

mitfuso.com

*rear fuel tank is not designed for use as a primary or auxiliary in any dual tank system
**133.9", 151.6", 169.3" wb

