

CANTER

FE180

SPECIFICATIONS

A boost for your business and your bottom line. The Canter® will change the way you think about moving your company forward. Its cost-of-ownership is so low you can measure it by the mile—in dramatically improved fuel economy, service intervals, payload capacity and driver productivity. Its fuel-injected diesel engine and automated manual transmission set new benchmarks for efficiency and driving ease. They're backed by our industry-best 5-Year/175,000-Mile powertrain limited warranty. The Canter FE180. It's just the boost your business needs.



Weight ratings	GVWR/GCWR	17,995 lb./25,710 lb.				
	GAWR (front/rear)	6,390 lb./12,700 lb.				
Curb weight	Base model	5,505 lb. (est.)				
	Estimated max.	12,490 lb. (see dealer for details)				
Body/Payload Dimensions	Wheelbases available	110.2"	133.9"	151.6"	169.3"	187.0"
	Overall length (cab/chassis)	204.1"	227.8"	245.5"	263.2"	280.9"
	Usable cab to rear axle	81.2"	104.9"	122.6"	140.3"	158.0"
	Body sizes accommodated	10' to 22' (23' with MFTA review/approval)				
	Model	4P10(T5)				
Engine	Type	DOHC, 4-cylinder, 4-stroke cycle, water-cooled, turbocharged, intercooled diesel with 4 valves per cylinder				
	Displacement	183 cu. in. (3.0 L)				
	Max. output (SAE, gross)	161 hp @ 3,400 rpm				
	Max. torque (SAE, gross)	295 lb.-ft. @ 1,300 rpm				
Air cleaner	Type	Dry paper element with snorkel				
Transmission	Standard equipment	Mitsubishi Fuso DUONIC® 6-speed OD AMT				
Axle capacity	Front	6,835 lb.				
	Rear	13,230 lb.				
Final reduction gear	Type	Single-reduction hypoid				
	Ratio	6.166				
Top speed, est.	Std diff	71 mph				
Turning diameter	Minimum, by wheelbase	34.1'	40.0'	44.6'	49.5'	54.1'
Tires (premium)	Configuration	Single front, dual rear				
	Size/Type	215/75R17.5 12PR LR:F hwy front/traction rear				
Wheels	Size/Configuration	17.5" x 6"/6-lug				
Steering	Type	Ball-nut type with integral-type hydraulic power boost				
	Adjustments	Tilt/telescoping steering column with steering lock				
Suspension	Front	Laminated leaf springs with shock absorbers and stabilizer bar				
	Rear	Laminated leaf springs with shock absorbers and stabilizer bar				
Brakes	Service	Dual-caliper discs, vacuum/hydraulic-type with ABS				
	Parking	Drum/driveline, internal expanding shoe				
	Exhaust	Electrically actuated				
Frame	Type	Ladder/straight				
	Section modulus	7.08 cu. in. per rail				
	Yield strength	56,565 psi				
	RBM per rail	400,410 lb.-in.				
	Height/Width	32.8"/33.5"				
Fuel tank	Capacity/Location—std.*	30 gal./in-frame, aft of rear axle				
	Capacity/Location—opt.**	33 gal./left side				
DEF tank	Capacity/Location	3.2 gal./right side				
Battery	Type/Capacity	Two 12-volt, maintenance-free/750 CCA				
Electrical	Starter/Alternator	12-volt/12-volt, 140A output				
Starting	Cold weather provision	Individual ceramic-tipped glow plugs				
Convenience/Assurance	Windows/Door locks	Power-operated, one-touch up and down driver's-side window				
	Cruise control	Standard (programmable)				
	Entry	Keyless, with driver/assistant door lock control				
	Radio	Optional Clarion AM/FM/CD Bluetooth radio				
	Engine Protection System (EPS)	Automatic engine shutdown due to low oil pressure; automatic fuel reduction due to excessive coolant temperature				
	Idle Limit System (ILS)—opt.	Automatic engine shutdown of stationary vehicle, in Park or Neutral, after achieving normal operating temperature with dealer-programmed limit of 3, 5 or 10 minutes				

SAFETY

Crush bar in each door, energy-absorbing steering column, daytime running lights, dual-caliper disc brakes with ABS (all wheels), covered open-grate entry steps, forward-swing doors for safer entry/exit, high-visibility halogen headlamps, Engine Protection System (EPS)

CAB COLORS

ARCADIA SILVER

NATURAL WHITE

JUPITER GREEN

MARS RED

SHANNON BLUE

SOLID BLACK

All models are available immediately in white. Other colors shown (except Solid Black) may be special-ordered at no extra charge. Accuracy of indicated hues is limited by paper/electronic reproduction.

FABRIC STYLE

BLUE CLOTH

Vehicle specifications are subject to change without notice. Photos and descriptions included in this spec sheet may vary in comparison to actual vehicle models. For warranty limitations and details, see your local dealer.

PRINTED IN THE U.S.A. 5/14.
©2014 MITSUBISHI FUSO TRUCK OF AMERICA, Inc.

Mitsubishi Fuso Truck of America, Inc.

2015 Center Square Road
Logan Township, NJ 08085

mitfuso.com

*rear fuel tank is not designed for use as a primary or auxiliary in any dual tank system
**133.9", 151.6", 169.3", 187.0" wb

